

Code Barre EAN13

Exemple d'édition d'une page A4 de code barre (EAN13)

PRTF :

600	A		R	RCD001			
700	A	80					SKIPB(001)
1100	A			WTC01	20	0	6
1200	A						FONT(1351)
1300	A						SPACEB(002)
1400	A			WTC02	20	0	33
1500	A						FONT(1351)
1600	A			WTC03	20	0	60
1700	A						FONT(1351)
1800	A			WLC01	30	0	8
1900	A						FONT(1051)
2000	A						SPACEB(001)
2100	A			WLC02	30	0	35
2200	A						FONT(1051)
2300	A			WLC03	30	0	62
2400	A						FONT(1051)
2500	A			WBC01	12S	0	7
2600	A						BARCODE(EAN13 4 *HRZ *HRI (*WIDTH 0-
2700	A						,016) (*RATIO 2,00))
2800	A						SPACEB(001)
2900	A			WBC02	12S	0	34
3000	A						BARCODE(EAN13 4 *HRZ *HRI (*WIDTH 0-
3100	A						,016) (*RATIO 2,00))
3200	A			WBC03	12S	0	61
3300	A						BARCODE(EAN13 4 *HRZ *HRI (*WIDTH 0-
3400	A						,016) (*RATIO 2,00))
3500	A	* 2					
18500	A	* 8					
18600	A			WTC022	20	0	6
18700	A						FONT(1351)
18800	A						SKIPB(062)
18900	A			WTC023	20	0	33
19000	A						FONT(1351)
19100	A			WTC024	20	0	60
19200	A						FONT(1351)
19300	A			WLC022	30	0	8
19400	A						FONT(1051)
19500	A						SPACEB(001)
19600	A			WLC023	30	0	35
19700	A						FONT(1051)
19800	A			WLC024	30	0	62
19900	A						FONT(1051)
20000	A			WBC022	12S	0	7
20100	A						BARCODE(EAN13 4 *HRZ *HRI (*WIDTH 0-
20200	A						,016) (*RATIO 2,00))
20300	A						SPACEB(001)
20400	A			WBC023	12S	0	34
20500	A						BARCODE(EAN13 4 *HRZ *HRI (*WIDTH 0-
20600	A						,016) (*RATIO 2,00))
20700	A			WBC024	12S	0	61
20800	A						BARCODE(EAN13 4 *HRZ *HRI (*WIDTH 0-
20900	A						,016) (*RATIO 2,00))

PF : code barre

R	CO	DB	OP	TEXT(Gestion des codes barres)
1	20	TCOD	20	Texte code barre
21	34	BCOD	14	Code barre
35	39	SCOD	5	Début code barre
40	69	LIB1	30	Libellé
70	99	LIB2	30	Libellé
100	100	TYPE	1	Type de code
101	101	FLAG	1	Flag édition
102	102	LOGO	1	Logo (O/N)

103	104	LOGS	2	Logo signe	
105	108	LOGL	4	Logo libellé	
109	118	NMR	10	Numéro	
P 119	122	CHR	6,0	K Chrono	
123	123	FUSE	1	Flag Utilisé	
124	133	CRTU	10	Crée par	
P 134	137	CRTD	7,0	Y le	
138	147	CRTW	10	sur	
P 148	150	NBI	5,0	4 Nombre d'impression	
151	160	MJU	10	Mis à jour par Util.	
161	170	MJW	10	sur (écran)	
P 171	174	MJD	7,0	Y le (date)	
P 175	178	MJH	6,0	à (heure)	EDTWRD(' : : ')
K		TYPE			
K		BCOD			

CL :

1000	PGM	PARM(&PRT &WNB)
1100		
1200	DCL	VAR(&PRT) TYPE(*CHAR) LEN(11)
1300	DCL	VAR(&WNB) TYPE(*CHAR) LEN(1)
1400		
1500	OVRPRTF	FILE(WECEB60) DEVTYPE(*IPDS) PAGESIZE(70) +
1600		PRTTXT(*BLANK) OUTQ(&PRT) SAVE(*YES)
1700		
1800	CALL	PGM(RECEB60) PARM(&WNB)
1900		
2000	ENDPGM	

RPGLE :

```

* Texte : 8405 14 361 5532 / écriture du code : *3615532 *
800      * Libellé : Coiffe pour casquette blanche
900      * sans logo Type B
1100     FWCEB60      0      E              PRINTER OFLIND(*IN99)
1200     F              INFDS(DSNBP)
1300     FPCODB0      IF      E              DISK
1400     *-----
1500     D DSNBP              DS
1600     D DSNB              154      155B 0
1700     *
1800     D              DS
1900     D WTC0              1      480
2000     D              DIM(24)
2100     D WTC01              1      20
2200     D WTC02              21      40
2300     D WTC03              41      60
2400     D WTC04              61      80
2500     D WTC05              81     100
2600     D WTC06             101     120
2700     D WTC07             121     140
2800     D WTC08             141     160
2900     D WTC09             161     180
3000     D WTC010            181     200
3100     D WTC011            201     220
3200     D WTC012            221     240
3300     D WTC013            241     260
3400     D WTC014            261     280
3500     D WTC015            281     300
3600     D WTC016            301     320
3700     D WTC017            321     340
3800     D WTC018            341     360
3900     D WTC019            361     380
4000     D WTC020            381     400
4100     D WTC021            401     420
4200     D WTC022            421     440
4300     D WTC023            441     460
4400     D WTC024            461     480
4500     D              DS
4600     D WBC0              1      288
4700     D              DIM(24)

```

4800	D	WBC01	1	12	0		
4900	D	WBC02	13	24	0		
5000	D	WBC03	25	36	0		
5100	D	WBC04	37	48	0		
5200	D	WBC05	49	60	0		
5300	D	WBC06	61	72	0		
5400	D	WBC07	73	84	0		
5500	D	WBC08	85	96	0		
5600	D	WBC09	97	108	0		
5700	D	WBC010	109	120	0		
5800	D	WBC011	121	132	0		
5900	D	WBC012	133	144	0		
6000	D	WBC013	145	156	0		
6100	D	WBC014	157	168	0		
6200	D	WBC015	169	180	0		
6300	D	WBC016	181	192	0		
6400	D	WBC017	193	204	0		
6500	D	WBC018	205	216	0		
6600	D	WBC019	217	228	0		
6700	D	WBC020	229	240	0		
6800	D	WBC021	241	252	0		
6900	D	WBC022	253	264	0		
7000	D	WBC023	265	276	0		
7100	D	WBC024	277	288	0		
7200	D		DS				
7300	D	WLC0	1	720			
7400	D				DIM(24)		
7500	D	WLC01	1	30			
7600	D	WLC02	31	60			
7700	D	WLC03	61	90			
7800	D	WLC04	91	120			
7900	D	WLC05	121	150			
8000	D	WLC06	151	180			
8100	D	WLC07	181	210			
8200	D	WLC08	211	240			
8300	D	WLC09	241	270			
8400	D	WLC010	271	300			
8500	D	WLC011	301	330			
8600	D	WLC012	331	360			
8700	D	WLC013	361	390			
8800	D	WLC014	391	420			
8900	D	WLC015	421	450			
9000	D	WLC016	451	480			
9100	D	WLC017	481	510			
9200	D	WLC018	511	540			
9300	D	WLC019	541	570			
9400	D	WLC020	571	600			
9500	D	WLC021	601	630			
9600	D	WLC022	631	660			
9700	D	WLC023	661	690			
9800	D	WLC024	691	720			
9900	*						
10000	C	*ENTRY	PLIST				
10100	C		PARM	WNB	1	qté à imprimer	
10200	C		Z-ADD	*ZEROS J	2 0		
10300	C		Z-ADD	*ZEROS I	2 0		
10400	*						
10500	D001 C		SELECT				
10600	001 C	WNB	WHENEQ	'1'			
10700	001 C		Z-ADD	1	NB	2 0	
10800	001 C	WNB	WHENEQ	'2'			
10900	001 C		Z-ADD	10	NB		
11000	F001 C		ENDSL				
11100	*						
11200	C	1	SETLL	CODB0P			
11300	D001 C	*IN36	DOWEQ	*OFF			
11400	001 C		READ	CODB0P		36	
11500	001 C	36	LEAVE				
11600	*						
11700	D002 C	FLAG	IFEQ	'*'			
11800	002 C	TYPE	ANDEQ	'C'			

11900	D003	C	DO	24	I	
12000	003	C	MOVEL(P)	BCOD	WBCO(I)	
12100	003	C	MOVEL(P)	TCOD	WTCO(I)	
12200	003	C	MOVEL(P)	LIB1	WLCO(I)	
12300	F003	C	ENDDO			
12400		*				
12500		C	SETOFF			80
12600	D003	C	DO	NB	J	
12700	003	C	WRITE	RCD001		
12800		C	SETON			80
12900	F003	C	ENDDO			
13000	002	C	LEAVE			
13100	F002	C	END			
13200		*				
13300	F001	C	ENDDO			
13400		*	-----			
13500		C	SETON			LR

X 12 N D'A

5901195



X 12 N D'A

5901195



X 12 N D'A

5901195



X 12 N D'A

5901195

